



AssuredSAN™

2333 - 4 Port iSCSI Storage System

BENEFITS



Scalable Performance

- Dual RAID controller (active/active)
- Data rates up to 1Gb/sec. iSCSI
- SimulCache™ - Low latency cache mirroring
- Up to 7 expansion units per system
- Max 96 drives, 288TB

Built in Redundancy

- RAID 0, 1, 5, 6, 10, 50
- Redundant, hot swap components
- Built-in schedule capability

Green Features

- EcoStor™ Economically and environmentally sound technologies
- Battery-free cache backup
- Drive-spin-down
- RoHS-6 and WEEE compliant

Virtualization

- Microsoft certified
- VMware compatible

1Gb iSCSI SAN SOLUTION

2 ports per controller, 4 per system

The AssuredSAN™ 2333 storage array is ideal for a small business Ethernet SAN, offering inexpensive expansion, support for Windows, Linux, and Mac OS X. AssuredSAN solutions combine performance and high capacity storage with the ease of the RAIDar™ management GUI which provides a complete set of features and tools to ensure easy set-up and management.

Just the Capacity You Need

The AssuredSAN 2333 has three simple configurations in a 2U chassis:

- 12 - 1 terabyte drives, for a 12 terabyte system

- 12 - 2 terabyte drives, for a 24 terabyte system

- 12 - 3 terabyte drives, for a 36 terabyte system

See page 2 for specific part numbers.

Ideal Applications

The AssuredSAN 2333 is an affordable choice for email, databases, file sharing, and backup targets.

Accelerated performance with SimulCache

The 2333 uses patented SimulCache™ technology that instantly and simultaneously mirrors cache between RAID controllers, leading to significant performance improvements over traditional implementations.

Green Features

The AssuredSAN 2333 features energy saving drive-spin-down which allows users to power down drives during off-peak hours, which can reduce both power and cooling expenses.

Utilizing Dot Hill's patented EcoStor™ technology, these systems have completely eliminated cache batteries, using instead super capacitors and flash memory to provide infinite cache backup during a power loss, while being environmentally friendly.



Storage Made Easy

AssuredSAN arrays are easy to configure and manage with RAIDar 2.0, our intuitive web based interface which provides storage setup and monitoring without the need for host based software. RAIDar 2.0 saves time with configuration and installation wizards.

- Easy to set up Configuration, Installation Wizards
- International Localization for Dutch, French, German, Italian, Spanish, Simplified Chinese, traditional Chinese, Japanese, and Korean. including translated online help.

support

Warranty

AssuredSANs come with a three year standard hardware warranty, a 90 day software warranty, and Bronze level support, which provides you with expert 24X7 technical telephone support, access to our SANsolve and the Customer Resource Center with knowledge base articles, product documentation and firmware upgrades.

Gold and Platinum Support Programs

Dot Hill is equipped to provide the extra level of support you may need to meet your service level agreements. Our Gold and Platinum levels of support are designed to offer maximum responsiveness anywhere in the world. These programs include options for same day advance shipment, parts depot access, next business day and 4-hour onsite service. We also offer extended hardware warranties and extended software support packages.

2333 models

The AssuredSAN 2333 is a hardware only model that ships with the storage array, drives, rail kit, cables, Installation Guide, and Bronze support.

Ordering the 2333

Arrays with 1,2, or 3TB drives Nearline SAS drives, 1Gb iSCSI host connections, dual controllers, and AC power

Part Numbers

D2333CN12007DA
D2333CN24007DA
D2333CN36007DA

Description

2333, 2RM, 1GB, 12 X 1TB SAS, 7K, AC, DH
2333, 2RM, 1GB, 12 X 2TB SAS, 7K, AC, DH
2333, 2RM, 1GB, 12 X 3TB SAS, 7K, AC, DH

Ordering JBODS

JBODs with 1, 2, or 3TB Nearline SAS drives, and AC power

Part Numbers

D3130CN12007DA
D3130CN24007DA
D3130CN36007DA

Description

3130, 2JM, 12 X 1TB SAS, 7K, AC, DH
3130, 2JM, 12 X 2TB SAS, 7K, AC, DH
3130, 2JM, 12 X 3TB SAS, 7K, AC, DH

PHYSICAL

Depth (excluding cables)	23.7 Inches / 60.2 cm
Height	3.5 Inches / 8.9 cm
Width	17.6 Inches / 44.7 cm

OEM Models

Available for volume OEM customers. An OEM Customization Kit is available which allows OEM customers to create their own branded storage solutions.

shipping information

Packaged product weight approximately 85.5 lbs with drives

Packaged product dimensions Width 25.5", Height 10", Depth 28.5"



HOSTS			
External Ports	4 iSCSI (Gigabit Ethernet) Dual Controller		
Host speed	1Gb iSCSI		
Initiators	All iSCSI compliant initiators		
Interface Type	RJ-45		
DRIVE SUPPORT			
2333	1 TB, 2TB, 3TB drive options		
EXPANSION			
3130	up to 8 (1 RAID, 7 JBOD), 96 drives		
CERTIFICATIONS			
Microsoft			
HIGH-AVAILABILITY FEATURES			
Redundant Hot-Swappable Controllers			
Redundant Hot-Swappable Disk, Fans, Power			
Dual Power Cords			
Hot Standby Spare			
Automatic Failover			
Multi-Path Support			
PROTOCOLS AND STANDARDS			
iSCSI (IETF)	ICMP (RFC 3720)		
SUPPORT			
Software Warranty	90 days		
Standard Hardware Warranty	3 years		
RAID			
Levels Supported	0, 1, 5, 6, 10 and 50		
SYSTEM CONFIGURATION			
Cache Memory	1GB per controller		
Cache Backup	Battery-free protection w/super capacitors		
Virtual disks per System	32		
Volumes per virtual disk	128		
Volumes per System	1024		
Mirrored Cache	Yes - SimulCache™		
Super Capacitor Cache Backup	Yes		
Cache Backup to Flash	Yes - Non-volatile		
MANAGEMENT			
Interface Types	10/100 Ethernet, Mini USB		
Protocols Supported	SNMP, SSL, SSH, SMTP, SMI-S Provider, HTTP(S)		
Management Consoles	WEB GUI, CLI		
Management Software	RAIDar 2.0		
Remote Diagnostics	Yes		
Non-disruptive Updates	Yes		
Non-disruptive Volume Expansion			
POWER REQUIREMENTS - AC INPUT			
Input Power Requirements	100-240VAC 50/60Hz		
Max Input Power	436W max maximum continuous per chassis		
Heat Dissipation	1488 BTUs/hour		
	Bronze Rated - high efficiency		
	82% @ 20% load		
	86% @ 80% load		
	85% @ 100% load		
TEMPERATURE AND HUMIDITY RANGES			
Operating Temperature	41°F to 104°F (5°C to 40°C)		
Shipping Temperature	-40°F to 158°F (-40°C to 70°C)		
	Note: Derate 2°C for every km, up to 3000 meters		
Operating Humidity	10% to 90% RH @ 104°F (40°C), non-condensing		
Non-Operating Humidity	Up to 93% RH @ 104°F (40°C) non-condensing		
DECLARED ACOUSTIC NOISE LEVELS			
Sound Power	LWAd=6,75 B		
Sound Pressure	LpAm - 55dB _A		
SHOCK AND VIBRATION			
Shock, Operational	5G's for 10 ms		
Shock, Non-Operational	15G 11ms, half sine		
Vibration, Operational	5Hz to 500Hz, 0.21Grms flat spectrum		
Vibration, Non-Operational	3-365-3Hz, 1.22 Grms, z-axis, 0.85 Grms, X&Y axis shaped spectrum		
REGULATORY			
Safety	UL 60950-1, 1st edition, 2007-10-31 (USA) CAN/CSA-C22.2 No.60950-1-03, 1st Edition, 2006-7 (Canada) EN 60950-1:2006 (European Union) EC 60950-1:2001 (International) EN 60950-1:2001 +A1:2004 (GS Mark, Germany) CCC Mark (power supply only, China PRC)		
Electromagnetic Compatibility			
Emissions	CFR 47 Part 15 Subpart B Class A (U.S.A.) ICES-003:2004 Class A (Canada) EN 55022:2006 +A1:2007 Class A (EU) EN 300 386 V1.4.1:2008 Class A (EU Telco) AS/NZS CISPR 22:2009 Class A (Australia, New Zealand) VCCI:2009-04 Class A (Japan) GOST R 51318.22-99 Class A (Russia) KN 22 Class A (S. Korea) CNS 13438:2006 Class A (Taiwan)		
Harmonics	EN61000-3-2:2006 (EU)		
Flicker	EN 61000-3-3:1995 +A1:2001+A2:2005 (EU)		
Immunity	EN 55024:1998 +A1:2001+A2:2003 (EU) EN 300 386 V1.4.1:2008 (EU Telco) GOST R 51318.24-99 (Russia) KN 24 (S. Korea)		
RoHS and WEEE	RoHS-6/6 Compliance, China RoHS, WEEE		
Country Approvals	United States, Canada, European Union (EU), Australia/New Zealand, Japan, China (PRC), Russia, Mexico, South Africa, Germany, South Korea, Taiwan		

* specifications subject to change at any time.

